



HP Latex 115 Print and Cut Solution

Start—with this easy, affordable 54-in HP Latex print and cut solution



The HP solution—best in its class¹

- Print more applications, full bleed stickers don't shrink or curl; reach indoor spaces solvent can't
- Enjoy accurate high-speed cutting and cut throughs; LAN connectivity and HP media basket add convenience
- Optimized workflow management from a single point—includes unique software with barcode integration
- Design applications in 3 simple steps—no design skills are needed with HP Signage Suite in box²

For more information, please visit hp.com/go/Latex115printandcut

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at hp.com/communities/LKC

Learn more at hp.com/go/latexprintos

True print AND cut

- Print AND cut at the same time—versus print OR cut with solvent—with this reliable, dual-device solution
- Avoid solvent wait time—prints come out dry, cut/laminate right away with no degas time, and deliver same day
- Avoid lamination for short-term applications—scratch resistance is comparable to hard-solvent inks³

Easy, reliable workflow

- Print and cut in 5 simple steps—add cut lines from the RIP, predefined cutting presets, easy user interface
- Efficient job recognition and reliable, error-free cutting—Optical Positioning System (OPOS) and HP Barcode
- Avoid the complexity of other dual-devices—this complete HP solution is designed to work as one

¹ Based on productivity and environmental advantages compared to the leading (per IDC market share numbers, March 2017) and comparably priced solvent-technology-based integrated print and cut solution. HP internal productivity testing performed February 2017. The HP Latex Print and Cut Solution also uses HP Latex inks that meet UL ECOLOGO® Certification to UL 2801, demonstrating that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see ul.com/EL).

² Requires an HP Applications Center account, Internet connection, and connected Internet-capable device. For more information, see <http://www.hpapplicationscenter.com>.

³ You can consider unlaminate use for short-term signage with scratch resistance comparable to hard-solvent inks on self-adhesive vinyl and PVC banner. Scratch-resistance comparison based on testing third generation HP Latex Inks and representative hard-solvent inks. Estimates by HP Image Permanence Lab on a range of media.

Technical specifications


Printing	Printing modes	48 m ² /hr (517 ft ² /hr) - Billboard (2 pass) 16 m ² /hr (174 ft ² /hr) - Outdoor Plus (6 pass) 12 m ² /hr (129 ft ² /hr) - Indoor Quality (8 pass) 10 m ² /hr (108 ft ² /hr) - Indoor High Quality (10 pass) 6 m ² /hr (65 ft ² /hr) - Backlits, Textiles, and Canvas (16 pass) 5 m ² /hr (54 ft ² /hr) - High Saturation Textiles (20 pass)	
	Print resolution	Up to 1200 x 1200 dpi	
	Ink types	HP Latex Inks	
	Ink cartridges	Black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer	
	Cartridge size	400 ml	
	Printheads	6 (2 cyan/black, 2 magenta/yellow, 1 light cyan/light magenta, 1 HP Latex Optimizer)	
	Color consistency ⁴	Average \leq 1 dE2000, 95% of colors \leq 2 dE2000	
	Media	Handling	Roll feed; take-up reel (optional); automatic cutter (for vinyl, paper-based media, backlit polyester film)
		Media types	Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas, synthetics, (fabrics, mesh, textiles, and any other porous materials that require a liner)
		Roll size	254 to 1371-mm (10 to 54-in) rolls; 580 to 1371-mm (23 to 54-in) rolls with full support
Roll weight		25 kg (55 lb)	
Roll diameter		180 mm (7.1 in)	
Thickness		Up to 0.5 mm (19.7 mil)	
Applications		Banners; Displays; Exhibition and event graphics; Exterior signage; Indoor posters; Interior decoration; Light boxes - film; Light boxes - paper; POP/POS; Posters; Vehicle graphics; Customizable clothing; Floor graphics; Labels and stickers; Wall decals; Window graphics	
Connectivity	Interfaces (standard)	Gigabit Ethernet (1000Base-T)	
Dimensions (w x d x h)	Printer	2307 x 840 x 1380 mm (91 x 33 x 54 in)	
	Shipping	2553 x 762 x 1252 mm (100.5 x 30 x 49.5 in)	
Weight	Printer	174 kg (384 lb)	
	Shipping	257.5 kg (568 lb)	
What's in the box	HP Latex 115 Printer; printheads; maintenance cartridge; printer stand; spindle; user maintenance kit; edge holders; quick reference guide; setup poster; power cords.		
Environmental ranges	Operating temperature	15 to 30°C (59 to 86°F)	
	Operating humidity	20 to 80% RH (non-condensing)	
Acoustic	Sound pressure	54 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep)	
	Sound power	7.2 B(A) (printing); 5.5 B(A) (ready); < 3.5 B(A) (sleep)	
Power	Consumption	2.2 kW (printing); 70 W (ready); < 2.5 W (sleep)	
	Requirements	Input voltage (auto ranging) 200-240 V (\pm 10%) two wires and PE; 50/60 Hz (\pm 3 Hz); two power cords; 3 A max for printer and 13 A max per curing	
Certification	Safety	IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC); Argentina (IRAM); China (CCC); India (BIS)	
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), Russia, Belarus, and Kazakhstan (EAC), China (CCC)	
	Environmental	ENERGY STAR; WEEE; RoHS (EU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT Bronze; OSHA; CE marking compliant	
Warranty	1 year, provided that the End of Installation Registration is completed by a HP authorized reseller or by the user, in case of customer installations. In this case, the online training must be completed by the customer and the printer must be connected to the Customer Involvement Program or Printer Data Sharing program, enabling the option of sending the printer's serial number if possible		

HP Latex 54 Basic Cutter

Cutting	Cut type	Drag-knife with TurboCut and Tangential emulsion modes	
	Cut width	135 cm (53.1 in)	
	Cut speed	Up to 84 cm/sec (33 in/sec) diagonal (113 cm/sec (44 in/sec) for media narrower than 737 mm (29 in))	
	Acceleration	Up to 0.9 G diagonal (3 G for media narrower than 737 mm/29 in)	
	Accuracy	0.2% of movement or 0.25 mm, (0.01 in) whichever is greater	
	Repeatability	\pm 0.1 mm (0.004 in)	
	Cut force	0 to 400 grams of downforce, in 5-gram steps	
	Cut thickness	0.05 to 0.25 mm (0.002 to 0.01 in); 0.8 mm (0.03 in) with optional sandblast blade	
	Connectivity	Interfaces (standard)	USB and Ethernet (LAN)
	Dimensions (w x d x h)	Cutter	1750 x 680 x 1145 mm (68.9 x 26.8 x 45.1 in)
Cutter (shipping)		1880 x 480 x 670 mm (74 x 18.9 x 26.4 in)	

Weight	Cutter	48 kg (106 lb)
	Cutter (shipping)	69 kg (152 lb)
What's in the box	HP Latex 54 Basic Cutter; cutter stand; media basket; HP FlexiPrint and Cut RIP; HP Cutter Control software; quick reference guide; setup poster; documentation software; power cords; standard holder (1); standard blades (2); cut-off knife (1); 3-in media flanges (set of 2)	
Environmental ranges	Operating temperature	15 to 35°C (59 to 95°F)
	Operating humidity	35 to 75% RH (non-condensing)
Acoustic	Sound pressure	56 dB(A)
	Sound power	7.0 B(A)
Power	Consumption	31 W (working mode)
	Requirements	AC 100-240 V (\pm 10%); 50/60 Hz, 85 VA max; 2 A
Certification	Safety	IEC 60950-1+A1+A2 compliant; USA (UL listed) and Canada; EU (LVD and EN 60950-1 compliant); PSE (Japan); Korea (KC)
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC)
	Environmental	WEEE, RoHS (EU); CE marking compliant; REACH
Warranty	1 year, provided that the End of Installation Registration is completed by a HP authorized reseller or by the user, in case of customer installations. In this case, the online training must be completed by the customer	

Ordering information

Product	1LH39A	HP Latex 115 Print and Cut Solution	
Accessories	1UP26A	HP Latex Cutter Extended Kit	
	1UP27A	HP Latex 2-in Media Holder Kit	
	1UX44A	HP Latex Standard Blade Kit	
	1UX45A	HP Latex Specialty Blade Kit	
	F0M55A	HP Latex 54-in Printer 2-in Spindle	
	F0M59A	HP Latex User Maintenance Kit	
	WSA60A	HP Latex 54-in Take-up Reel	
	F0M64A	HP Series 300/500 Edge Holders Kit	
	Original HP printheads	CZ677A	HP 831 Cyan/Black Latex Printhead
		CZ678A	HP 831 Yellow/Magenta Latex Printhead
CZ679A		HP 831 Light Magenta/Light Cyan Latex Printhead	
CZ680A		HP 831 Latex Optimizer Printhead	
Original HP ink cartridges and maintenance supplies		GOY86A	HP 821 400-ml Cyan Latex Ink Cartridge
		GOY87A	HP 821 400-ml Magenta Latex Ink Cartridge
		GOY88A	HP 821 400-ml Yellow Latex Ink Cartridge
		GOY89A	HP 821 400-ml Black Latex Ink Cartridge
	GOY90A	HP 821 400-ml Light Cyan Latex Ink Cartridge	
	GOY91A	HP 821 400-ml Light Magenta Latex Ink Cartridge	
	GOY92A	HP 821 400-ml Latex Optimizer Ink Cartridge	
	CZ681A	HP 831 Latex Maintenance Cartridge	
Original HP large format printing materials	HP printing materials are designed together with HP Latex Inks and HP Latex printers to provide optimal image quality, consistency, and reliability.		
	HP PVC-free Wall Paper (FSC® and UL GREENGUARD GOLD Certified) ⁵		
	HP Permanent Gloss Adhesive Vinyl (REACH compliant) ⁶		
	HP Backlit Polyester Film 		
	HP Premium Satin Canvas		
For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com .			
Service and support	U9TS3E	HP 2 year Next Business Day with Defective Media Retention	
	U9TS4E	HP 3 year Next Business Day with Defective Media Retention	
	U9TS7PE	HP 1 year Post Warranty Next Business Day with Defective Media Retention	
	U9TS8PE	HP 2 year Post Warranty Next Business Day with Defective Media Retention	

⁴ The color variation inside a printed job has been measured to be within this limit: maximum color difference (95% of colors) \leq 2 dE2000. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard D5 014-6/E:2012. 5% of colors may experience variations above 2 dE2000. Backlit substrates measured in transmission mode may yield different results.

⁵ BMG trademark license code FSC®-C115319, see fsc.org. HP trademark license code FSC®-C017543, see fsc.org. Not all FSC®-certified products are available in all regions. UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg or greenguard.org.

⁶ This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.

⁷ HP Large Format Media take-back program availability varies. Recycling programs may not exist in your area. See HPLFMedia.com/hp/ecosolutions for details.



NOTE: Some certifications may only apply to the printer

